

# ISO/TS 18198:2023-03 (E)

## Determination of long-term flow of geosynthetic drains

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Test equipment and procedures for determination of short-term in- plane water flow .....</b>	<b>1</b>
4.1	Measurement of maximum hydraulic transmissivity and flow rate .....	1
4.2	Test equipment .....	2
4.2.1	Unidirectional flow .....	2
4.2.2	Index and performance tests .....	5
4.3	Normal compressive loading and seating time .....	5
4.4	Number of test specimens per sample per test .....	6
4.5	Hydraulic gradient .....	7
<b>5</b>	<b>Determination of long-term flow performance .....</b>	<b>7</b>
5.1	General .....	7
5.2	Reduction factors (RF) .....	8
5.3	Reduction factor for intrusion (RF,in and RF,GI) .....	9
5.4	Reduction factor for creep (RF,cr) .....	10
5.4.1	General .....	10
5.4.2	Time-temperature superposition methods .....	11
5.5	Reduction factors for chemical clogging (RF,CC) and biological clogging (RF,BC) .....	12
5.6	Additional considerations .....	13
5.6.1	Design life .....	13
5.6.2	Design temperature .....	13
5.6.3	Installation damage .....	14
5.6.4	Durability of the polymers .....	14
<b>6</b>	<b>Alternative procedures to determine Qa .....</b>	<b>14</b>
6.1	General .....	14
6.2	Long-term reduction of water flow capacity due to compressive creep by the BAM (Germany) method .....	14
6.3	Thickness-dependent short-term flow testing using SIM .....	17
6.4	Time dependent loading followed by flow capacity measurements .....	19
Bibliography .....		20