DIN EN 13492:2006-10 (E)

Geosynthetic barriers - Characteristics required for use in the construction of liquid waste dispo sal sites, transfer stations or secondary containment

Contents

Page

Introduction 5

1 Scope 6

2 Normative references 6

3 Definitions and abbreviations 8
3.1 Definitions 8
3.2 Abbreviations 9

4 Required characteristics and corresponding methods of test 9
4.1 General 9
4.2 Relevant characteristics 9
4.3 Characteristics relevant to specific conditions of use 12
4.3.1 Tear strength 12
4.3.2 Bursting strength 12
4.3.3 Friction characteristics (direct shear and inclined plane tests) 12
4.3.4 Low temperature behaviour 12
4.3.5 Weathering 12
4.3.6 Resistance to wetting and drying 12
4.3.7 Freeze-thaw cycle resistance 13
4.3.8 Resistance to root penetration 13

5 Evaluation of conformity 13
5.1 Presentation of characteristics 13
5.2 Verification of values 13
5.3 Initial type tests 13
5.4 Factory production control 14
5.5 Inspection 14

6 Marking 14

Annex A (normative) Scheme of factory production control 15

A.1 Product design 15
A.2 Production 15
A.3 Finished products 15
A.4 Equipment 15
A.5 Provisions applicable to A.1, A.2 and A.3 (to be used where appropriate) 16

Annex B (normative) Durability of geosynthetic barriers 17

B.1 Introduction 17
B.2 Evaluation of durability tests and acceptance criteria 18
B.3 Weathering 18
B.3.1 Direct tests 18
B.3.2 Period of exposure 19
B.4 Resistance to micro-organisms 20
B.5 Resistance to root penetration 20
B.6 Resistance to environmental stress cracking 20
B.7 Resistance to leaching 21

B.8 Resistance to oxidation 21
B.9 Chemical resistance for landfill applications 21
B.9.1 All applications 21
B.10 Geosynthetic clay barriers 22

Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive 23

ZA.1 Scope and relevant characteristics 23

ZA.2 System of attestation of conformity for Geomembranes used in the construction of liquid waste disposal sites, transfer stations and secondary containment 24

ZA.3 CE marking and labelling 26

Bibliography 30

Figures Figure ZA.1 -- Example of CE marking on the packaging of a Geosynthetic Barrier 27

Figure ZA.2 -- Example of accompanying documents 28

Tables Table 1 -- Geosynthetic Barriers used in the construction of liquid waste disposal sites, transfer stations and secondary containment - Functions, function-related characteristics and test methods to be used 10

Table 2 -- Characteristics required for initial type testing and evaluation of conformity 14

Table B.1 -- Required weathering radiant exposure (> 75 % retained tensile properties) 20

Table ZA.1 -- Scope and relevant clauses 24

Table ZA.2 -- System of attestation of conformity 25

Table ZA.3 -- Assignation of evaluation of conformity tasks (for geosynthetic barriers under system 2+) 25