

# DIN SPEC 4867:2022-04 (E)

## Cleaning test methods for the abrasion resistance of glass coatings for solar applications; Text English

---

### Contents

	Page
Foreword .....	4
Introduction.....	6
1 Scope .....	7
2 Normative references .....	7
3 Terms and definitions.....	7
4 Symbols and abbreviations.....	8
4.1 Symbols .....	8
4.2 Abbreviations .....	8
5 Apparatus .....	9
5.1 Test apparatus .....	9
5.2 Samples .....	10
5.3 Brushing parameters for coating abrasion resistivity testing (working mode 1).....	11
5.4 Auxiliary material and dust-water suspension .....	12
5.4.1 Working mode 1: coating abrasion resistivity testing.....	12
5.4.2 Working mode 2: brush and brushing parameter assessment.....	13
5.5 Reflection measurement equipment.....	13
6 Test procedure .....	14
6.1 Preparation of samples and apparatus .....	14
6.2 Test parameters.....	14
6.2.1 General .....	14
6.2.2 Working mode 1: coating abrasion resistivity testing.....	15
6.2.3 Working mode 2: brush and brushing parameter assessment.....	15
6.3 Procedures.....	15
6.3.1 Working mode 1: coating abrasion resistivity testing.....	15
6.3.2 Working mode 2: brush and brushing parameter assessment.....	16
7 Measurement .....	17
7.1 Sampling parameters.....	17
7.2 Measurement parameters.....	18
8 Evaluation of the reflectance data .....	19
9 Test report .....	20
Annex A (normative) Calibration .....	22
A.1 Calibration of the washing equipment.....	22
A.2 Determination of the deposited dust quantity in g/m <sup>2</sup> .....	24
Annex B (informative) Example for the integral reflection change.....	25
Bibliography.....	26

### Figures

Figure 1 — Schematic of test setup .....	9
--	---

<b>Figure 2 — Scheme with reflectance measurements positions for samples with a minimum size of 0,8 m × 1,6 m .....</b>	<b>17</b>
<b>Figure 3 — Scheme with reflectance measurement positions for samples with a size &lt; 0,8 m × 1,6 m.....</b>	<b>18</b>
<b>Figure A.1 — Schematic top view of the cardboard positioning procedure for the detection of the right side of the spray pattern .....</b>	<b>23</b>
<b>Figure A.2 — Example spray pattern and dimensions that shall be achieved during calibration of the washing equipment.....</b>	<b>23</b>
<b>Figure B.1 — Median absolute (left) relative (right) integral effective reflectance change value vs. number of brushing strokes .....</b>	<b>25</b>

## **Tables**

<b>Table 1 — Symbols.....</b>	<b>8</b>
<b>Table 2 — Predefined particle diameter distribution of feldspar test dust for coating abrasion resistivity testing.....</b>	<b>12</b>