DIN SPEC 91437:2023-05 (E)

Liquid Organic Hydrogen Carrier (LOHC) based on toluene - Evaluation, testing and assurance of LOHC quality; Text in English

Contents

Page

Foreword . . . 3
Introduction . . . 4
1 Scope . . . 5
2 Normative references . . . 5
3 Terms and definitions . . . 5
4 Description of LOHC technology . . . 6
5 Requirements for usage as LOHC . . . 7
5.1 General . . . 7
5.2 LOHC-0 material . . . 8
5.2.1 Material properties . . . 8
5.2.2 Further substances . . . 8
5.3 Working LOHC material . . . 8
5.3.1 General . . . 8
5.3.2 LOHC-H material . . . 9
5.3.3 LOHC-D material . . . 9
6 Test methods . . . 10
6.1 General . . . 10
6.2 Material properties . . . 10
6.3 Further substances . . . 10
Annex A (normative) **Nominal material properties of the described LOHC systems** . . . 12
Annex B (informative) **Definition of LOHC side products/other hydrocarbons** . . . 13
Annex C (informative) **Example for the determination of the degree of hydrogenation** . . . 14
Annex D (informative) **Exemplary test protocol and retention times for purity and hydrocarbon analysis** . . . 15
Bibliography . . . 16

Figures

Figure 1 — General concept of the LOHC-technology . . . 7

Tables

Table 1 — LOHC-O material properties at 20 °C . . . 8
Table 2 — Limits for contamination of LOHC-0 material . . . 8
Table 3 — LOHC-H material properties at 20 °C . . . 9
Table 4 — Limits for contamination of LOHC-H material . . . 9
Table 5 — LOHC-D material properties at 20 °C . . . 9
Table 6 — Limits for contamination of LOHC-D material . . . 10
Table A.1 — Nominal values of density in regard to the degree of hydrogenation (DoH) (properties at 20 °C) . . . 12
Table A.2 — Nominal values of dynamic viscosity in regard to the degree of hydrogenation (DoH) (properties at 20 °C) . . . 12