

# DIN SPEC 91437:2023-05 (E)

## Liquid Organic Hydrogen Carrier (LOHC) based on toluene - Evaluation, testing and assurance of LOHC quality; Text in English

---

### Contents

	Page
Foreword . . . . .	3
Introduction . . . . .	4
1 Scope . . . . .	5
2 Normative references . . . . .	5
3 Terms and definitions . . . . .	5
4 Description of LOHC technology . . . . .	6
5 Requirements for usage as LOHC . . . . .	7
5.1 General . . . . .	7
5.2 LOHC-0 material . . . . .	8
5.2.1 Material properties . . . . .	8
5.2.2 Further substances . . . . .	8
5.3 Working LOHC material . . . . .	8
5.3.1 General . . . . .	8
5.3.2 LOHC-H material . . . . .	9
5.3.3 LOHC-D material . . . . .	9
6 Test methods . . . . .	10
6.1 General . . . . .	10
6.2 Material properties . . . . .	10
6.3 Further substances . . . . .	10
Annex A (normative) Nominal material properties of the described LOHC systems . . . . .	12
Annex B (informative) Definition of LOHC side products/other hydrocarbons . . . . .	13
Annex C (informative) Example for the determination of the degree of hydrogenation . . . . .	14
Annex D (informative) Exemplary test protocol and retention times for purity and hydrocarbon analysis . . . . .	15
Bibliography . . . . .	16

### Figures

Figure 1 — General concept of the LOHC-technology . . . . .	7
---	---

### Tables

Table 1 — LOHC-0 material properties at 20 °C . . . . .	8
Table 2 — Limits for contamination of LOHC-0 material . . . . .	8
Table 3 — LOHC-H material properties at 20 °C . . . . .	9
Table 4 — Limits for contamination of LOHC-H material . . . . .	9
Table 5 — LOHC-D material properties at 20 °C . . . . .	9
Table 6 — Limits for contamination of LOHC-D material . . . . .	10
Table A.1 — Nominal values of density in regard to the degree of hydrogenation (DoH) (properties at 20 °C) . . . . .	12
Table A.2 — Nominal values of dynamic viscosity in regard to the degree of hydrogenation (DoH) (properties at 20 °C) . . . . .	12