DIN DKE SPEC 99200:2025-03 (E)

ReqIF™ interpretation for public standards - Release 1.3; Text in English

Inhalt

Seite

Foreword 7

Introduction 8

1 Scope 9

2 Normative references 9

3 Terms and definitions 10

4 Challenges 11

5 Objectives 12

6 Target software 12

7 Application best-practice 13
7.1 Internal standard versus interchange format 13
7.2 Configuration issues for target software 13
7.3 Digital material for the import and export process 14
7.4 Conforming application 14

8 Data model 15
8.1 Structural overview 15
8.1.1 Information on the provision (SpecObject) 15
8.1.2 Attributes on the document SpecObject for asset or service metadata of the creator, supplier, or publisher 16
8.2 Attributes 18
8.2.1 Information on the provision (SpecObject) 18
8.2.2 Attributes on the document SpecObject for asset or service metadata of the creator, supplier, or publisher 25
8.3 Lists of attribute values 26
8.3.1 Standard element (obj.element-name) 26
8.3.2 Language (obj.language) 28
8.3.3 Modality; bindingness (obj.modality) 30
8.3.4 Normativity; context status (obj.normativity) 30
8.3.5 SpecObject type (obj.specobj-type) 31
8.3.6 Business process (use.business-process) 31
8.3.7 Business sector; industry sector (use.business-sector) 32
8.3.8 Interaction (use.interaction) 33
8.3.9 Implementation region (use.location) 34
8.3.10 Project phase (use.project-phase) 37
8.3.11 Product life cycle (use.product-life-cycle) 38
8.3.12 Purpose; intention; focus (use.purpose) 38
8.4 Long name and identifier syntax 39
8.4.1 Datatype definitions (DataTypeDefinitions) 39
8.4.2 Specification types (SpecTypes) 49
8.4.3 Specifications 54
8.4.4 Specifications Objects (SpecObjects) 54
8.4.5 Specification relations (SpecRelations) 54
8.4.6 Specification relation groups (SpecRelationGroups) 54
8.5 Class name abbreviations (in long names and identifiers) 55

9 Semantic interoperability 55

9.1 Attribute conventions 55
9.1.1 Data field term; data field designation 55
9.1.2 ReqIF™ attribute name 55
9.1.3 ReqIF™ data type 56
9.1.4 ReqIF™ attribute value 56
9.1.5 Default value for attributes 56
9.1.6 Definition for attribute names and attribute values 56
9.1.7 Overflow of attribute values 56
9.1.8 Localization of attributes 57
9.2 Attribute or content outputs 57
9.2.1 Data field term or definition (ReqIF:DESC) 57
9.2.2 Identifier (ReqIF:IDENTIFIER) 58
9.2.3 ReqIF™ attribute name (ReqIF:LONG-NAME) 58
9.2.4 ReqIF™ attribute value (ReqIF:LONG-NAME) 58
9.2.5 Definition (ReqIF:DESC) 59
9.2.6 Is-editable (ReqIF:IS-EDITABLE) 59
9.2.7 Last change (ReqIF:LAST-CHANGE) 59
9.2.8 Maximum length (ReqIF:MAX-LENGTH) 59
9.2.9 Value list using multiple or single values (ReqIF:MULTI-VALUED) 59
9.2.10 Other content (ReqIF:OTHER-CONTENT) 59
9.3 File format 60
9.3.1 Form of the ReqIF™ file 60
9.3.2 Header of the ReqIF™ file 60
9.3.3 Tool extensions 61
9.4 Fragmentation of documents into provisions (SpecObjects) 61
9.4.1 Fragmentation options 61
9.4.2 Sentence determination 61
9.4.3 “Atomic element” 62
9.4.4 “Terminating element” 63
9.4.5 Enumerations (lists) in the text 63
9.5 Modality; bindingness 64
9.5.1 Determining the modality (obj.modality) 64
9.5.2 Modalities related to context 65
9.5.3 Bindingness of the modality values 65
9.5.4 Review of the modality (obj.modality) 66
9.5.5 Align the modality (obj.modality) 66
9.6 Content attributes (ReqIF.*) 66
9.6.1 Heading (ReqIF.ChapterName) 66
9.6.2 Content (ReqIF.Text) 66
9.7 Object attributes (obj.*) 67
9.7.1 Clause heading (obj.clause-heading) 67
9.7.2 Clause context (obj.clause-number) 67
9.7.3 Reliability (obj.conversion-reliability) 67
9.7.4 Standard element (obj.element-name) 68
9.7.5 Modality (obj.modality) 68
9.7.6 Language (obj.language) 68
9.7.7 Normativity (obj.normativity) 68
9.7.8 SpecObject type (obj.specobject-type) 69
9.7.9 Conversion issues (obj.transformation-issues) 69
9.8 Use attributes for intra-company management (use.*) 69
9.8.1 Business process (use.business-process) 69
9.8.2 Business sector; industry sector (use.business-sector) 69
9.8.3 Date usage begins (use.date-usage-begins) 70
9.8.4 Date usage ends (use.date-usage-ends) 70
9.8.5 Interaction (use.interaction) 70
9.8.6 Implementation region (use.location) 70
9.8.7 Project phase (use.project-phase) 70
9.8.8 Product category (use.product-category) 70

9.8.9 Product life cycle (use.product-life-cycle) ... 70
9.8.10 Purpose; intention; focus (use.purpose) ... 71
9.9 Bibliographic document metadata (bib.*) ... 71
9.10 Identifier (ID) attributes (ids.*) ... 71
9.10.1 Document ID ... 71
9.10.2 Element ID ... 71
9.10.3 Language-independent ID ... 71
9.10.4 Path-IDs ... 72
9.10.5 Version-independent tracing ID ... 72
9.10.6 Version-dependent unique ID ... 72
9.11 Document asset or service metadata of the creator, supplier, or publisher (pub.*) ... 73
9.11.1 Originator (pub.originator) ... 73
9.11.2 Harmonization (pub.harmonization) ... 73
9.11.3 Software (pub.software) ... 73
9.11.4 Supplier (pub.supplier) ... 73

10 Presentation ... 73
10.1 Change marks in the text ... 73
10.2 Labelling and numbering ... 73
10.2.1 Output position of the label ... 73
10.2.2 Presentation aspects for labels ... 74
10.3 Figures and other types of graphics ... 74
10.3.1 Types of graphics ... 74
10.3.2 Graphics format ... 75
10.3.3 Graphics compression ... 75
10.3.4 Graphics resolution ... 75
10.4 Formulas ... 75
10.4.1 Formula format ... 75
10.4.2 Formula output ... 75
10.4.3 Dissolve in-line formulas ... 76
10.5 Footnotes ... 76
10.6 Tables ... 77
10.6.1 Table format ... 77
10.6.2 Table output ... 77
10.6.3 Normalization of tables ... 77

11 Digital material to the ReqIF™ interpretation for public standards ... 77
11.1 Benchmarking ... 77
11.2 Examples ... 78
11.3 Tables to the data model ... 78
11.4 Utilities for the import and export processes (scripts or templates) ... 78
11.5 Validating the data model release 1.3 (Schematron) ... 78

Annex A (informative) User stories for requirements engineering ... 79

Annex B (informative) Background on identifiers (IDs) ... 80
B.1 User Stories for identifiers (IDs) ... 80
B.2 Initial situation for ID systems ... 80
B.3 Challenges regarding multiple ID systems ... 80
B.4 Recommendations for maintaining multiple ID systems ... 80

Annex C (normative) Determination of the normativity (obj.normativity) ... 82

Annex D (informative) Determination of the conversion reliability (obj.conversion-reliability) ... 83

Bibliography ... 84

Figures

Figure 1 — *n* to *n* communication ... 13

Figure 2 — *n* via 1 communication **13**

Figure 3 — Data model to the ReqIF™ interpretation for public standards **15**

Tables

Table 1 — Content attributes **18**

Table 2 — Object attributes **19**

Table 3 — Use attributes **20**

Table 4 — Bibliographic document metadata **22**

Table 5 — Identification (ID) attributes **24**

Table 6 — Attributes on the document SpecObject **26**

Table 7 — Values for the attribute obj.element-name **27**

Table 8 — Values for the attribute obj.language **28**

Table 9 — Values for the attribute obj.modality **30**

Table 10 — Values for the attribute obj.normativity **31**

Table 11 — Values for the attribute obj.specobj-type **31**

Table 12 — Values for the attribute use-business-process **32**

Table 13 — Values for the attribute use.business-sector **32**

Table 14 — Values for the attribute use.interaction **34**

Table 15 — Values for the attribute use.location **34**

Table 16 — Values for the attribute use.project-phase **37**

Table 17 — Values for the attribute use.product-life-cycle **38**

Table 18 — Values for the attribute use.purpose **38**

Table 19 — DataTypeDefinitions **39**

Table 20 — RelationGroupTypes **49**

Table 21 — SpecificationTypes **49**

Table 22 — SpecObjectTypes **50**

Table 23 — SpecRelationTypes **54**

Table 24 — Class name abbreviations **55**

Table 25 — Setting of values depending on the SpecObjectType **69**